

NEW
HIGH OUTPUT
HIGH CRI

AREA 48 LED™

THE PERFECT SOFT LIGHT

BBS LIGHTING brings you a major break-through in LED Technology.

The AREA-48 LED represents the next-generation in lighting technology for studio and location work. BBS's new integrated LED technology moves the phosphor away from the LED itself, thereby greatly improving color rendering, consistency, and light output. The system's color rendering accuracy is over 95 CRI, with HD-friendly soft light output comparable to a 1K traditional soft light, and multiple power options including an integrated battery or standard AC power. Moreover, the phosphor panels themselves are interchangeable, allowing you to quickly change the fixture from Daylight to Tungsten, to Chroma-Green, all in a matter of seconds.

BBS's AREA-48 LED: High-Output, Great Color, and the option to Run on Batteries

AREA 48 LED Features


- **Ultra High CRI: Chroma Green 525n, 95 CRI 2700k , 97 CRI 3200k, 95 CRI 4300k, 96 CRI 5600k, 95 CRI 6500k and Chroma Blue Phosphor Panels**
- **Extremely high light output**
- **V-Mount or Gold Mount (AB) battery options**
- Wide 160° light dispersion (95° w/optional softbox)
- Flicker-free dimming from 100%-0
- Silent operation (no fan)
- Internal DMX512 for remote control
- Special effects strobing mode
- Very compact, versatile unit



AREA 48 Fixture Includes

- 3200K or 5600K High CRI phosphor panel
- Integrated barndoors
- Angled yoke with 5/8" female baby pin TVMP
- 160W power supply & AC power cord

RUNS ON AC OR INTEGRATED BATTERY



AREA 48 LED Specifications

POWER

AC Power: 100-240V 50/60Hz
Max Power Consumption: 122W
Battery Operational Voltage Range: 12-20V

LED

Premium LED Array - 50K hour life

CONTROL


Manual or Internal DMX512
DMX in/out for daisy-chaining
8/16 bit dimming 100%-0
Up to 4 control channels in 16 bit mode, selectable via digital display

DIMENSIONS

W: 356mm / 13.97"
H: 275mm / 10.82"
D: 115mm / 4.53"
Weight: 3.6kg / 7.94 lbs

THERMAL

Ambient Operating Temperature:
0-40°C / 0-104°F



AREA 48 Brackets available to assemble 1X2, 2x2 or 9 Area 48 Lights in a 8X8 frame with optional Soft Boxes and Grids



www.BBSLighting.com
+1 800.820.6610

AREA 48 LED™

THE PERFECT SOFT LIGHT



Runs on AC
or Batteries

ADDITIONAL INFORMATION

Options

Chroma Green 525n, 95 CRI 2700k, 97 CRI 3200k, 95 CRI 4300k,


96 CRI 5600k and 95 CRI 6500k phosphor panels

Phosphor panel carrying case


V-Mount or Gold Mount (AB) battery plates

DoPchoice Snapgrid™ and Snapbox softboxes and grids


Wide 160° to 40° Light Dispersion Pattern



Standard
Beam Angle



With optional
Soft Box



With optional
Snap Grid

Product Benefits

- Wide spectrum quality soft light with visually accurate color temperature
- Flexible AC or DC power options
- Smooth dimming from 100% to 0 with no color shift
- Flicker-free performance at any frame rate or shutter angle
- Microprocessor controlled current management for long LED life
- Efficient power management for low power consumption and high reliability

Area 48 5600K (CRI 96 Phosphor Panel)

160 Degree Beam Angle						
Distance Feet	3	6	10	12	16	20
Footcandles	385	96	36	22	13	9
Distance Meters	1	2	3	4	5	6
LUX	4147	1037	386	240	139	96

Area 48 3200K (CRI 97 Phosphor Panel)

160 Degree Beam Angle						
Distance Feet	3	6	10	12	16	20
Footcandles	361	90	34	21	12	8
Distance Meters	1	2	3	4	5	6
LUX	3882	970	361	225	130	90

Area 48 5600K with optional DP Choice Soft-box

Approx. 95 Degree Beam Angle						
Distance Feet	3	6	10	12	16	20
Footcandles	736	184	68	43	25	17
Distance Meters	1	2	3	4	5	6
LUX	7921	1980	737	459	265	184

Area 48 3200K with optional DP Choice Soft-box

Approx. 95 Degree Beam Angle						
Distance Feet	3	6	10	12	16	20
Footcandles	657	164	61	38	22	15
Distance Meters	1	2	3	4	5	6

For more information please
visit www.bbslighting.com

AREA 48 LED™



www.BBSLighting.com
+1 800.820.6610