

# Celeb® 400 DMX LED



The Celeb® 400 DMX joins Kino Flo's line of LED lighting systems. With soft, even True Match® light quality (CRI 95), the Celeb 400 boasts technical innovations that make it an ideal professional imaging tool: dial-in white light from 2700 to 5500 Kelvin and presets with programmable settings. Light levels do not change when selecting Kelvin settings. The Celeb also includes full range dimming without color shift.

The Celeb 400 DMX operates at universal input from 100VAC-240VAC or 24VDC. The slim profile fixture produces more lumens than a 1K tungsten softlight, yet uses only 1.8A (120VAC) compared to a tungsten softlight at 8.3A. The Celeb comes with molded accessory holders, removable gel frame and focusing louver.

Features include:

- Kelvin presets and custom settings between 2700-5500K
- Universal input 100VAC-240VAC or 24VDC
- Onboard and DMX dimming
- Flicker-free, dead quiet operation
- Gel Frame and Honeycomb Louver
- Center Mount, Yoke Mount and Pole-Op

## ▼ Celeb 400 DMX LED Center




**CEL-400C-120U**  
Celeb 400 DMX  
Center Mount, Univ 120U

**CEL-400C-230U**  
Celeb 400 DMX  
Center Mount, Univ 230U



**GFR-CE4**  
Celeb 400 Gel Frame  
(Included)



**LVR-CE490-P**  
Celeb 400 Louver/HP, 90°  
(Included)



**MTP-LM**  
Kino 81 Lollipop w/  
Junior Pin (28mm)  
(Included)

## ▼ Celeb 400 DMX LED Yoke



**CEL-400Y-120U**  
Celeb 400 DMX  
Yoke Mount, Univ 120U

**CEL-400Y-230U**  
Celeb 400 DMX  
Yoke Mount, Univ 230U




**CEL-400P-120U**  
Celeb 400 DMX  
Pole-Op, Univ 120U

**CEL-400P-230U**  
Celeb 400 DMX  
Pole-Op, Univ 230U



**GFR-CE4**  
Celeb 400 Gel Frame  
(Included)



**LVR-CE490-P**  
Celeb 400 Louver/HP, 90°  
(Included)

▼ Photometrics

	FC	687	220	105	61	40	28	21	16	13	11
	Feet	2	4	6	8	10	12	14	16	18	20
<b>Celeb 400</b>	LUX	9800	3423	1647	958	634	442	331	258	208	168
	Meters	0.5	1	1.5	2	2.5	3	3.5	4	4.5	5

▼ Fixture Specifications

Fixture	Input Voltage VAC	Amps VAC	Input Voltage VDC	Amps VDC	Kelvin Range	Dimming Range	Dimensions	Weight
<b>Celeb 400 DMX Center</b>	100-240VAC, 50/60Hz, 210W	1.8A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	45 x 14 x 5" (114.5 x 36 x 13cm)	26 lb (12kg)
<b>Celeb 400 DMX Center</b>	240-100VAC, 50/60Hz, 207W	1.0A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	45 x 14 x 5" (114.5 x 36 x 13cm)	26 lb (12kg)
<b>Celeb 400 DMX Yoke</b>	100-240VAC, 50/60Hz, 210W	1.8A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	50 x 16.5 x 5" (127 x 42 x 13cm)	26 lb (12kg)
<b>Celeb 400 DMX Yoke</b>	240-100VAC, 50/60Hz, 207W	1.0A	18-28VDC, 198W	8.25A	2700-5500	100%-1%	50 x 16.5 x 5" (127 x 42 x 13cm)	26 lb (12kg)

▼ Details



Bill Roe



Bill Roe



Bill Roe

▼ Celeb 400 DMX LED Kits



**KIT-C4-120U**  
Celeb 400 DMX Center Mount Kit, Univ 120U

**KIT-C4-230U**  
Celeb 400 DMX Center Mount Kit, Univ 230U

**Contents**  
1 Celeb 400 DMX Center  
1 Flight Case

**Dimensions**  
53.5 x 11 x 16.5"  
(136 x 28 x 42cm)  
**Weight**  
52.5 lb (24kg)



**KIT-C4Y-120U**  
Celeb 400 DMX Yoke Mount Kit, Univ 120U

**KIT-C4Y-230U**  
Celeb 400 DMX Yoke Mount Kit, Univ 230U

**Contents**  
1 Celeb 400 DMX Yoke  
1 Jr. Pin  
1 Ship Case

**Dimensions**  
53.5 x 9 x 23.5"  
(136 x 23 x 60cm)  
**Weight**  
53 lb (24kg)

▼ Celeb 400 DMX LED Accessories/ Cases



**BRD-CE4**  
Celeb 400 Barndoors  
(Set of 4)



**LVR-CE460P**  
Celeb 400 Louver/HP, 60°



**MTP-180**  
Junior Pin Assembly  
for Yoke (28mm)



**MTP-CE**  
Celeb Support w/ Pin



**7010045**  
Celeb 400  
Yoke Assembly



**7010046**  
Celeb 400  
Pole-Op Assembly



**KAS-CE4**  
Celeb 400 Center Flight Case



**KAS-CE4-C**  
Celeb 400 Center Travel Case



**KAS-CE4-S**  
Celeb 400 Center Ship Case

**KAS-CE4-Y**  
Celeb 400 Yoke Ship Case