

Celeb® 200 DMX LED



The Celeb® 200 DMX LED fixture features the cool, energy efficient qualities that lighting professionals have come to expect from Kino Flo. The Celeb also boasts technical innovations that make it an ideal professional imaging tool: a dial-in variable color temperature control, full-range dimming and programmable 2700K to 5500K presets. Light levels do not change when selecting Kelvin settings.

Like the vaunted, award-winning line of portable Kino Flos, the Celeb 200 reproduces color faithfully, beautifully on HD or film, in the studio or on location. The Celeb's 100 Watts of soft, lustrous white light doesn't flicker or shift color temperature when dimmed. The trim, lightweight DMX fixture operates on universal AC power or battery power, and needs only one amp (120VAC) to produce more lumens than a 750W tungsten soft light.

The Celeb's cost savings from low energy and long lamp life continues Kino Flo's reputation as an environmentally friendly lighting company. The Celeb 200 comes complete with 360 degree mounting, molded accessory holders, removable gel frame and focusing louver.

Features include:

- Kelvin presets and custom settings between 2700-5500K
- Universal Input 100VAC-240VAC or 24VDC
- Onboard and DMX dimming
- Flicker-free, dead quiet operation
- Center Mount, Yoke Mount and Pole-Op
- Gel Frame and Honeycomb Louver

▼ Celeb 200 DMX LED Center



CEL-200C-120U
Celeb 200 DMX
Center Mount, 120U

CEL-200C-230U
Celeb 200 DMX
Center Mount, 230U



GFR-CE2
Celeb 200 Gel Frame
(Included)



LVR-CE290-P
Celeb 200 Louver/HP 90°
(Included)



MTP-LB
Kino 41 Lollipop w/
Baby Receiver (16mm)
(Included)

▼ Celeb 200 DMX LED Yoke



CEL-200Y-120U
Celeb 200 DMX
Yoke Mount, 120U

CEL-200Y-230U
Celeb 200 DMX
Yoke Mount, 230U



CEL-200P-120U
Celeb 200 DMX
Pole-Op, 120U

CEL-200P-230U
Celeb 200 DMX
Pole-Op, 230U



GFR-CE2
Celeb 200 Gel Frame
(Included)



LVR-CE290-P
Celeb 200 Louver/HP 90°
(Included)

▼ Photometrics

FC	349	95	45	24	16	11	8
Feet	2	4	6	8	10	12	14
Celeb 200							
LUX	5501	1507	678	381	245	172	127
Meters	0.5	1	1.5	2	2.5	3	3.5

▼ Fixture Specifications

Fixture	Input Voltage VAC	Input Voltage VDC	Dimming Range	Amps VAC	Amps 24VDC	Dimensions	Weight
Celeb 200C	100–240VAC, 50/60Hz, 100W	18–28VDC, 100W	1%–100%	0.96A	4A	24 x 14 x 5" (61 x 35.5 x 12.7cm)	15 lb (6.8kg)
Celeb 200C	240–100VAC, 50/60Hz, 100W	18–28VDC, 100W	1%–100%	0.54A	4A	24 x 14 x 5" (61 x 35.5 x 12.7cm)	15 lb (6.8kg)
Celeb 200Y	100–240VAC, 50/60Hz, 100W	18–28VDC, 100W	1%–100%	0.96A	4A	28.5 x 16.5 x 5" (72.3 x 42 x 12.7cm)	16 lb (7.3kg)
Celeb 200Y	240–100VAC, 50/60Hz, 100W	18–28VDC, 100W	1%–100%	0.54A	4A	28.5 x 16.5 x 5" (72.3 x 42 x 12.7cm)	16 lb (7.3kg)

▼ Details



Checco Varese



Matt Libatique



Mike Bauman/Mihai Malaimare

▼ Celeb 200 DMX LED Kit



KIT-C2-120U

Celeb 200 DMX Center Mount Kit, 120U

KIT-C2-230U

Celeb 200 DMX Center Mount Kit, 230U

Contents

- 1 Celeb 200
- 1 Flight Case

Dimensions

28 x 10 x 17"
(71.1 x 25.4 x 43.1cm)

Weight

31 lb (14kg)


▼ Celeb 200 DMX LED Accessories / Cases



BRD-CE2
Celeb 200 Barndoors
(Set of 4)



STD-M30
Medium Duty, 3-Rise 30°



LVR-CE260-P
Celeb 200 Louver/HP 60°



7010032
Celeb 200
Yoke Assembly



MTP-180
Junior Pin Assembly
for Yoke (28mm)



7010038
Celeb 200
Pole-Op Assembly



MTP-140
Baby Receiver Assembly
for Yoke (16mm)



KAS-CE2
Celeb 200 Flight Case



MTP-841F
Kino Offset w/ Baby Receiver
(16mm)



KAS-CE2-C
Celeb 200 Travel Case